

Rules and Regulations

Federal Register

Vol. 80, No. 212

Tuesday, November 3, 2015

This section of the FEDERAL REGISTER contains regulatory documents having general applicability and legal effect, most of which are keyed to and codified in the Code of Federal Regulations, which is published under 50 titles pursuant to 44 U.S.C. 1510.

The Code of Federal Regulations is sold by the Superintendent of Documents. Prices of new books are listed in the first FEDERAL REGISTER issue of each week.

DEPARTMENT OF TRANSPORTATION

Federal Aviation Administration

14 CFR Part 25

[Docket No. FAA-2015-2123; Special Conditions No. 25-604-SC]

Special Conditions: TIMCO Aerosystems, Boeing Model 777-300ER Series Airplanes; Dynamic Test Requirements for Single-Occupant, Oblique (Side-Facing) Seats with Airbag Devices

AGENCY: Federal Aviation Administration (FAA), DOT.

ACTION: Final special conditions; request for comments.

SUMMARY: These special conditions are issued for Boeing Model 777-300ER series airplanes. This airplane, as modified by TIMCO Aerosystems, will have novel or unusual design features associated with oblique-angled, single-occupant seats equipped with airbag systems. The applicable airworthiness regulations do not contain adequate or appropriate safety standards for these design features. These special conditions contain the additional safety standards the Administrator considers necessary to establish a level of safety equivalent to that established by the existing airworthiness standards.

DATES: The effective date of these special conditions is November 3, 2015. We must receive your comments by December 18, 2015.

ADDRESSES: Send comments identified by docket number FAA-2015-2123 using any of the following methods:
Federal eRegulations Portal: Go to <http://www.regulations.gov/> and follow the online instructions for sending your comments electronically.

Mail: Send comments to Docket Operations, M-30, U.S. Department of Transportation (DOT), 1200 New Jersey Avenue SE., Room W12-140, West

Building Ground Floor, Washington, DC 20590-0001.

Hand Delivery or Courier: Take comments to Docket Operations in Room W12-140 of the West Building Ground Floor at 1200 New Jersey Avenue SE., Washington, DC, between 9 a.m. and 5 p.m., Monday through Friday, except Federal holidays.

Fax: Fax comments to Docket Operations at 202-493-2251.

Privacy: The FAA will post all comments it receives, without change, to <http://www.regulations.gov/>, including any personal information the commenter provides. Using the search function of the docket Web site, anyone can find and read the electronic form of all comments received into any FAA docket, including the name of the individual sending the comment (or signing the comment for an association, business, labor union, etc.). DOT's complete Privacy Act Statement can be found in the **Federal Register** published on April 11, 2000 (65 FR 19477-19478), as well as at <http://DocketsInfo.dot.gov/>.

Docket: Background documents or comments received may be read at <http://www.regulations.gov/> at any time. Follow the online instructions for accessing the docket or go to Docket Operations in Room W12-140 of the West Building Ground Floor at 1200 New Jersey Avenue SE., Washington, DC, between 9 a.m. and 5 p.m., Monday through Friday, except Federal holidays.

FOR FURTHER INFORMATION CONTACT: John Sheldon, Airframe and Cabin Safety, ANM-115, Transport Airplane Directorate, Aircraft Certification Service, 1601 Lind Avenue SW., Renton, Washington 98057-3356; telephone 425-227-2785; facsimile 425-227-1149.

SUPPLEMENTARY INFORMATION: The FAA has determined that notice of, and opportunity for, prior public comment on these special conditions are impracticable because these procedures would significantly delay issuance of the design approval and thus delivery of the affected airplane.

In addition, the substance of these special conditions has been subject to the public-comment process in several prior instances with no substantive comments received. The FAA therefore finds that good cause exists for making these special conditions effective upon issuance.

Comments Invited

We invite interested people to take part in this rulemaking by sending written comments, data, or views. The most helpful comments reference a specific portion of the special conditions, explain the reason for any recommended change, and include supporting data.

We will consider all comments we receive by the closing date for comments. We may change these special conditions based on the comments we receive.

Background

On August 20, 2014, through FAA project no. ST14746AT-T, certification plan no. 13T422R006, TIMCO Aerosystems applied for a supplemental type certificate to allow the installation of oblique passenger seats, positioned at 30 degrees to the vertical plane of the airplane longitudinal centerline, and to include inflatable lap belts, in Boeing Model 777-300ER airplanes. The Boeing Model 777-300ER airplane is a wide-body, swept-wing, conventional-tail, twin-engine, turbofan-powered transport airplane, with seating capacity for 550 passengers and 11 crew members.

TIMCO Aerosystems proposes the installation of oblique (side-facing) B/E Aerospace Super Diamond Business Class (B/C) seats. These seats will include airbag devices for occupant restraint and injury protection.

Type Certification Basis

Under the provisions of § 21.101, TIMCO Aerosystems must show that the 777-300ER, as changed, continues to meet the applicable provisions of the regulations listed in type certificate no. T00001SE, or the applicable regulations in effect on the date of application for the change, except for earlier amendments as agreed upon by the FAA. The regulations listed in the type certificate are commonly referred to as the "original type-certification basis." The regulations listed in type certificate no. T00001SE are as follows:

The type-certification basis for the Model 777-300ER airplane is 14 CFR part 25, effective February 1, 1965, as amended by Amendments 25-1 through 25-98, including special conditions 25-295-SC and 25-187A-SC. In addition, the certification basis includes certain special conditions, exemptions, or later

amended sections of the applicable part that are not relevant to these proposed special conditions.

If the Administrator finds that the applicable airworthiness regulations (*i.e.*, 14 CFR part 25) do not contain adequate or appropriate safety standards for the Boeing Model 777–300ER airplane because of a novel or unusual design feature, special conditions are prescribed under the provisions of § 21.16.

Special conditions are initially applicable to the model for which they are issued. Should the applicant apply for a supplemental type certificate to modify any other model included on the same type certificate to incorporate the same novel or unusual design feature, these special conditions would also apply to the other model under § 21.101.

In addition to the applicable airworthiness regulations and special conditions, the Boeing Model 777–300ER airplane must comply with the fuel-vent and exhaust-emission requirements of 14 CFR part 34, and the noise-certification requirements of 14 CFR part 36.

The FAA issues special conditions, as defined in 14 CFR 11.19, in accordance with § 11.38, and they become part of the type-certification basis under § 21.101.

Novel or Unusual Design Features

The Boeing Model 777–300ER airplane will incorporate the following novel or unusual design features:

Installation of B/E Aerospace Super Diamond Business Class (B/C) seats manufactured by B/E Aerospace in “J” class, to be installed at an angle of 30 degrees to the airplane centerline. These seats will include airbag devices for occupant restraint and injury protection. The applicable airworthiness regulations do not contain adequate or appropriate safety standards for occupants of seats installed in the proposed configuration.

The seating configuration TIMCO Aerosystems proposes is novel and unusual due to the seat installation at 30 degrees to the airplane centerline, the airbag-system installation, and the seat/occupant interface with the surrounding furniture that introduces occupant alignment and loading concerns.

Ongoing research is progressing to establish acceptable occupant-injury limits. Until those limits become available, the FAA proposes a set of interim limits based on the current literature available, current National Highway Traffic Safety Administration (NHTSA) regulations, and preliminary test data from the research program.

The existing regulations do not provide adequate or appropriate safety standards for occupants of oblique-angled seats with airbag systems. To provide a level of safety that is equivalent to that afforded occupants of forward- and aft-facing seats, additional airworthiness standards, in the form of special conditions, are necessary. These special conditions supplement part 25 and, more specifically, supplement §§ 25.562 and 25.785. The requirements contained in these special conditions consist of both test conditions and injury pass/fail criteria.

Discussion

Amendment 25–15 to part 25, dated October 24, 1967, introduced the subject of side-facing seats, and a requirement that each occupant in a side-facing seat must be protected from head injury by a safety belt and a cushioned rest that will support the arms, shoulders, head, and spine.

Subsequently, Amendment 25–20, dated April 23, 1969, clarified the definition of side-facing seats to require that each occupant of a seat, positioned at more than an 18-degree angle to the vertical plane of the airplane longitudinal centerline, must be protected from head injury by a safety belt and an energy-absorbing rest that will support the arms, shoulders, head, and spine; or by a safety belt and shoulder harness that will prevent the head from contacting any injurious object. The FAA concluded that an 18-degree angle would provide an adequate level of safety based on tests that were performed at that time, and thus adopted that standard.

Part 25 was amended June 16, 1988, by Amendment 25–64, to revise the emergency-landing conditions that must be considered in the design of the airplane. Amendment 25–64 revised the static-load conditions in 14 CFR 25.561, and added the new § 25.562 that requires dynamic testing for all seats approved for occupancy during takeoff and landing. The intent of Amendment 25–64 is to provide an improved level of safety for occupants on transport-category airplanes. Because most seating is forward-facing on transport-category airplanes, the pass/fail criteria developed in Amendment 25–64 focused primarily on these seats. As a result, the FAA issued Policy Memorandums ANM–03–115–30 and PS–ANM–100–2000–00123 to provide the additional guidance necessary to demonstrate the level of safety required by the regulations for side-facing seats, and their mounting plates and adapters.

Special conditions 25–295–SC were issued on August 9, 2005, for the Boeing

Model 777, with injury criteria for seats installed at an oblique angle; however, those injury criteria were developed for a seat configuration that provided body support for the occupant, and do not directly address the complex occupant-loading conditions introduced by the oblique seat configuration that is the subject of these new special conditions.

To reflect current research findings, the FAA developed a methodology to address all fully side-facing seats (*i.e.*, seats positioned in the airplane with the occupant facing 90 degrees to the vertical plane of the airplane centerline), and has documented those requirements in a set of new special conditions. The FAA issued Policy Statement PS–ANM–25–03–R1 to define revised injury criteria associated with neck and leg injuries as they relate to fully side-facing seats, *i.e.*, seats installed 90 degrees to the airplane centerline. That policy statement does not address oblique seat installations. Some of those criteria are applicable to oblique seats but others are not, because the motion of an occupant in an oblique seat is different from the motion of an occupant in a fully side-facing seat during emergency-landing conditions.

Most recently, on September 30, 2015, the FAA issued special conditions 25–594–SC and 25–596–SC, applicable to the Boeing 747–8 and 777–200, for oblique seats. These new special conditions are identical to both of those special conditions. No public comments were received for those special conditions.

Applicability

As discussed above, these special conditions are applicable to the Boeing Model 777–300ER airplane. Should TIMCO apply at a later date for a supplemental type certificate to modify any other model included on type certificate no. T00001SE, to incorporate the same novel or unusual design feature, these special conditions would apply to the other model as well.

Conclusion

This action affects only certain novel or unusual design features on one model of airplane. It is not a rule of general applicability, and affects only the applicant who applied to the FAA for approval of these features on the airplane.

The substance of these special conditions has been subjected to the notice and comment period in several prior instances, and has been derived without substantive change from those previously issued. It is unlikely that prior public comment would result in a significant change from the substance

contained herein. Therefore, because a delay would significantly affect the certification of the airplane, the FAA has determined that prior public notice and comment are unnecessary and impracticable, and good cause exists for adopting these special conditions upon publication in the **Federal Register**. The FAA is requesting comments to allow interested persons to submit views that may not have been submitted in response to the prior opportunities for comment described above.

List of Subjects in 14 CFR Part 25

Aircraft, Aviation safety, Reporting and recordkeeping requirements.

The authority citation for these special conditions is as follows:

Authority: 49 U.S.C. 106(g), 40113, 44701, 44702, 44704.

The Special Conditions

■ Accordingly, pursuant to the authority delegated to me by the Administrator, the following special conditions are issued as part of the type certification basis for the Boeing Model 777–300ER airplane as modified by TIMCO Aerosystems.

Side-Facing Seats Special Conditions

In addition to the requirements of § 25.562:

1. Head-Injury Criteria

Compliance with § 25.562(c)(5) is required, except that, if the anthropomorphic test device (ATD) has no apparent contact with the seat/structure but has contact with an airbag, a head-injury criterion (HIC) unlimited score in excess of 1000 is acceptable, provided the HIC15 score (calculated in accordance with 49 CFR 571.208) for that contact is less than 700.

2. Body-to-Wall/Furnishing Contact

If a seat is installed aft of structure (e.g., an interior wall or furnishing) that does not provide a homogenous contact surface for the expected range of occupants and yaw angles, then additional analysis and/or test(s) may be required to demonstrate that the injury criteria are met for the area that an occupant could contact. For example, if different yaw angles could result in different airbag performance, then additional analysis or separate test(s) may be necessary to evaluate performance.

3. Neck Injury Criteria

The seating system must protect the occupant from experiencing serious neck injury. The assessment of neck injury must be conducted with the airbag device activated, unless there is

reason to also consider that the neck-injury potential would be higher for impacts below the airbag-device deployment threshold.

a. The N_{ij} (calculated in accordance with 49 CFR 571.208) must be below 1.0, where $N_{ij} = F_z/F_{zc} + M_y/M_{yc}$, and N_{ij} critical values are:

i. $F_{zc} = 1530$ lb for tension

ii. $F_{zc} = 1385$ lb for compression

iii. $M_{yc} = 229$ lb-ft in flexion

iv. $M_{yc} = 100$ lb-ft in extension

b. In addition, peak upper-neck F_z must be below 937 lb of tension and 899 lb of compression.

c. Rotation of the head about its vertical axis, relative to the torso, is limited to 105 degrees in either direction from forward-facing.

d. The neck must not impact any surface that would produce concentrated loading on the neck.

4. Spine and Torso Injury Criteria

a. The shoulders must remain aligned with the hips throughout the impact sequence, or support for the upper torso must be provided to prevent forward or lateral flailing beyond 45 degrees from the vertical during significant spinal loading. Alternatively, the lumbar spine tension (F_z) cannot exceed 1200 lb.

b. Significant concentrated loading on the occupant's spine, in the area between the pelvis and shoulders during impact, including rebound, is not acceptable. During this type of contact, the interval for any rearward (X-direction) acceleration exceeding 20g must be less than 3 milliseconds as measured by the thoracic instrumentation specified in 49 CFR part 572, subpart E, filtered in accordance with SAE International (SAE) J211–1.

c. Occupant must not interact with the armrest or other seat components in any manner significantly different than would be expected for a forward-facing seat installation.

5. Longitudinal test(s), conducted to measure the injury criteria above, must be performed with the FAA Hybrid III ATD, as described in SAE 1999–01–1609. The test(s) must be conducted with an undeformed floor, at the most-critical yaw case(s) for injury, and with all lateral structural supports (armrests/walls) installed.

Note: TIMCO Aerosystems must demonstrate that the installation of seats via plinths or pallets meets all applicable requirements. Compliance with the guidance contained in FAA Policy Memorandum PS–ANM–100–2000–00123, dated February 2, 2000, titled “Guidance for Demonstrating Compliance with Seat Dynamic Testing for Plinths and Pallets,” is acceptable to the FAA.

Inflatable Lap Belt Special Conditions

If inflatable lap belts are installed on single-place side-facing seats, the lap belts must meet Special Conditions no. 25–187A–SC.

Issued in Renton, Washington, on October 28, 2015.

Michael Kaszycki,

Acting Manager, Transport Airplane Directorate, Aircraft Certification Service.

[FR Doc. 2015–27936 Filed 11–2–15; 8:45 am]

BILLING CODE 4910–13–P

DEPARTMENT OF TRANSPORTATION

Federal Aviation Administration

14 CFR Part 25

[Docket No. FAA–2015–3368; Special Conditions No. 25–603–SC]

Special Conditions: Embraer Model EMB–545 and EMB–550 Airplanes; Occupant Protection For Side-Facing Seats Forward of Aft-Facing Seats

AGENCY: Federal Aviation Administration (FAA), DOT.

ACTION: Final special conditions; request for comments.

SUMMARY: These special conditions are issued for Embraer Model EMB–545 and EMB–550 airplanes. These airplanes will have a novel or unusual design feature associated with a seat configuration of side-facing seats positioned forward of aft-facing seats, and with a structural armrest between the side-facing and aft-facing seats. The applicable airworthiness regulations do not contain adequate or appropriate safety standards for this design feature. These special conditions contain the additional safety standards that the Administrator considers necessary to establish a level of safety equivalent to that established by the existing airworthiness standards.

DATES: The effective date of these special conditions is November 3, 2015. We must receive your comments by December 18, 2015.

ADDRESSES: Send comments identified by docket number FAA–2015–3368 using any of the following methods:

- *Federal eRegulations Portal:* Go to <http://www.regulations.gov/> and follow the online instructions for sending your comments electronically.

- *Mail:* Send comments to Docket Operations, M–30, U.S. Department of Transportation (DOT), 1200 New Jersey Avenue SE., Room W12–140, West Building Ground Floor, Washington, DC 20590–0001.